



Safety Data Sheet

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Revision Date: 02/22/2023
Revision 08 Replaces All Previous Safety Data Sheets.

Section 1 - Chemical Product and Company Identification

1.1 Product Name: Nitro 50-50

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Race Fuel

1.5 RESTRICTIONS ON THE USE: THIS FUEL IS FOR RACING VEHICLE USE ONLY!
NOT LEGAL FOR STREET-DRIVEN MOTOR VEHICLES.

1.6 Emergency Telephone: CHEMTREC 1-800-424-9300

International Emergency Telephone Number: +1-703-527-3887

1.7 See Section 16.3 for CHEMTREC in Country Emergency Numbers

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard

Categories

Highly Flammable	Category 2
Specific Target Organ Toxicity repeated exposure	Category 2
Specific Target Organ Toxicity single exposure	Category 2
Carcinogenicity	Category 1B
Eye Irritation	Category 2A
Acute Toxicity (Oral)	Category 3
Acute Toxicity (Inhalation)	Category 3
Acute Toxicity (Dermal)	Category 3
Reproductive toxicity	Category 2
Harmful to aquatic life with long-lasting effects	Category 3

GHS Classification Scale 1= severe hazard; 4= slight hazard

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System



Flame Health Hazard Irritant Toxic

2.2 Pictograms:

2.3 Signal Word **Danger**

2.4 Hazard Statements

PHYSICAL HAZARDS:

H225: Highly flammable liquid and vapor.

HEALTH HAZARDS:

H301: Toxic if swallowed.
H311: Toxic in contact with skin.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H351: Suspected of causing cancer (Inhalation).
H361: Suspected of damaging fertility or the unborn child.
H370: Causes damage to organs.
H373: May cause damage to organs through prolonged or repeated exposure to Blood and thyroid.

ENVIRONMENTAL HAZARDS:

H412: Harmful to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.
P201: Obtain special instructions before using this SDS.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from sparks and open flames- No smoking.
P223: Keep the container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe vapors and mist.
P264: Wash hands thoroughly after use.
P270: Do not eat, drink, or smoke when using this product.
P271: Use only outdoor or well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves, clothing, and eye

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System protection.

RESPONSE STATEMENTS:

P301 +310+ P331: IF SWALLOWED: USA
Immediately call the National POISON CENTER at **800-222-1222**. **OUTSIDE USA:** Immediately call the poison center or doctor. DO NOT induce vomiting.
P304+340: IF INHALED: Remove to fresh air and keep comfortable for breathing.
P305+P351: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present, and safe to do so. Continue rinsing.
P308+P313: If exposed or concerned, get medical attention.
P313+P337: If eye irritation occurs, get medical attention.
H314: Get medical attention if you feel unwell.
P330: Rinse mouth.
P362+364: Take off contaminated clothing and wash before reuse
P370+P378: In case of fire, use foam, carbon dioxide, or dry chemical to extinguish the fire.

STORAGE STATEMENTS:

P403+P233+P235: Store in a well-ventilated place. Keep the container tightly closed and cool.
P405: Store locked up.

DISPOSAL STATEMENTS:

P501: Dispose of content and container per local, regional, national, and international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Ocular eye irritation from vapors inflammation can occur. When splashed in the eye, the liquid may cause burning pain and transient corneal injury. **IF IN THE EYES: Rinse cautiously with water for at least 15 minutes.** Repeated liquid exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC #	Chemical Names	Percent	Classification
75-52-5	200-876-6	Nitromethane	50%	Flam. Liq. 3 H226, Acute Tox. 4, H302, Eye Irrit. 2 H319, Acute Tox. 4 H332, Car.2 H351, Repr. 2 H361 STOT SE 2 H371, STOT RE 2 H373, Acute Chronic H412
67-56-1	200-659-6	Methanol	50%	Flam, Lig. 2 H225, Acute Tox 3 H301, Acute Tox.3 H311, Acute Tox.3, H331, STOT SE 1 H370

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 4 - First Aid Measures

4.1 Description of First Aid Measures.

4.1.1 General information: Ensure medical personnel knows the material(s) involved and take precautions to protect themselves.

4.1.2 Following Inhalation: Remove the victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

4.1.3 Following Skin contact: Flush skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.1.4 Following eye contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.1.5 Following ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

4.2.2: Prolonged and repeated liquid contact with the skin can cause defatting and drying, leading to irritation and dermatitis.

4.2.3: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting, leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

4.2.4: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

4.3 Indication of any immediate medical attention and special treatment needed: The severity of outcome following exposure may be related to the time between the exposure and treatment rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

Note to Physicians: If you determine that a medical emergency exists. The specific chemical identity is necessary for emergency or first-aid treatment and will be immediately disclosed the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

General fire hazards: Highly flammable liquid and vapor.

5.1 Extinguishing media:

Suitable extinguishing media: Water fog. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Unsuitable extinguishing media: Do not use a water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture: Vapors may form explosive mixtures with air. Vapors may travel a considerable distance to a source of ignition and flashback. During a fire, gases hazardous to health may be formed.

5.3 Advice for firefighters: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Additional information: Do not release runoff from fire to sewers or waterways.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment, and emergency procedures:

6.1.1 For non-emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spills and leaks. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.1.2 For emergency responders: Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

6.2 Environmental precautions: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways.

6.3 Methods and material for containment and cleaning up:

6.3.1 For containment: Eliminate all ignition sources (no smoking, flares, sparks, or flames in the immediate area). Keep combustibles such as wood, paper, and oil) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water's surface. Prevent entry into waterways, sewers, basements, or confined areas.

6.3.2 For clean-up:

6.3.2.1 Small spill: Absorb with earth, sand, or other non-combustible material and transfer to containers for later disposal. Clean the surface thoroughly to remove residual contamination.

6.3.2.2 Large spill: Stop the material flow if this is without risk. Contain the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place it into a container for later disposal. Following product recovery, flush the area with water.

6.3.3 Other information: Never return spills to original containers for reuse. Put material in suitable, covered, labeled containers.

6.4 Reference to other sections: See section 8 of the SDS for personal protection. For waste disposal, see section 13 of the SDS.

Section 7 - Handling and Storage

7.1 Precautions for safe handling: Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Avoid contact with eyes. Observe good industrial hygiene practices. Provide adequate ventilation. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

immediate area., Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Avoid release to the environment. Observe good industrial hygiene practices.

7.1.1 Bonding and grounding plastic containers:

When bonding and grounding two non-conductive containers, a static electrical charge can be generated when two dissimilar materials (Metal and Plastic) pass quickly by one another; their many factors affect the size and strength of the static charge or potential that may develop, such as transfer speed, humidity, and container size. Therefore, the transfer of flammable liquids between plastic or other non-conductive containers should be under the following conditions:

1. A non-conductive container must be equipped with an approved metallic suction pump and draw tube for taking liquid from the top of a plastic container. The pump must be electrically grounded.
2. The non-conductive container must have a metallic, self-closing faucet that can be grounded electrically.

Additionally, flammable liquids between small containers may not require special bonding and grounding techniques. NFPA 77-1993 states that glass containers or other non-conductive materials of five gallons or less capacity are usually filled without special precautions." However, NFPA 77-1993 suggests that special techniques should handle flammable liquids in plastic containers with 5 to 60 gallons for larger containers would consider compliance with NFPA 77-1993 regarding the Bonding and grounding of plastic containers holding flammable liquids.).

7.2 Conditions for safe storage, including incompatibilities: Store locked up in a cool, dry, well-ventilated place out of direct sunlight. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a tightly closed container. Store in a. Store away from incompatible materials (see section 10).

7.3 Specific end use(s): Racing fuel only.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH TLV	OSHA - PELs
Nitromethane	20 ppm TWA	100 ppm TWA
Methanol	20ppm TWA	200ppm TWA

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded."

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below the OSHA PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder them before reuse. Remove this material from your shoes and clean personal protective equipment.

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows appropriate air-purifying respirators, use a full-face respirator with a multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Fluorinated rubber.

Splash contact: Fluorinated rubber.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, and the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Various

Odor: Sweet, aromatic Alcohol Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1.): 0.80

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not applicable

Water Solubility: Not Available

Melting point/freezing point: Not Available

Flash Point: 52°F (11°C) c.c Estimated

Boiling Point / Range: 149°F, 65°C

Lower Explosive Limits (vol % in air): Not Available

Upper Explosive Limits (vol % in air): Not Available

Viscosity: Not Available

Autoignition Temperature: Not Available

Decomposition temperature: Not Available

pH: Not Available

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

10.3 Hazardous Decomposition Products: Combustion produces carbon monoxide, aldehydes, aromatic, and other hydrocarbons.

10.4 Conditions to Avoid: Avoid shock, heat, sparks, open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 97 mg/kg

ATE (Dermal): 540.5 mg/kg.

ATE (Inhalation vapor/mist): 4.87mg/l

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause Toxic Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause Toxic Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause Toxic Inhalation Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

11.3 Aspiration Hazard: The European Chemical Agency Database shows that no components of this product may be fatal if swallowed and entered the airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no components of this product cause skin irritation. However, repeated exposure may cause skin irritation.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause serious eye irritation.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency Database show components of this product cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Test results found in the European Chemical Agency Database show no components of this product cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single exposure): The European Chemical Agency Database shows that components of this product may cause damage to the respiratory system.

11.11 Specific Target Organ Toxicity (Repeated Exposure): Contains chemicals that may cause damage to the following organs: Blood and thyroid.

11.12 Signs and Symptoms: Effects due to exposure may include Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, and Seizures. Symptoms may be delayed.

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause cancer.

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Nitromethane	IC50 36 mg/l	Algae	72 hours
Nitromethane	EC50 450 mg/l	Daphnia	24 hours
Nitromethane	LC50 460 mg/l	Fish	58 hours
Methanol	LC50 29.4 g/l	Fish	96 hours
Methanol	LC50 22,200 mg/l	Daphnia magna	48 hours

Toxicity OECD Guideline Test results found in the European Chemical Agency Database show components of this product cause harmful long-term toxicity to aquatic life.

12.2 Persistence and degradability: Persistence is unlikely.

12.3 Bioaccumulative potential: No data available.

12.4 Mobility: Will likely be mobile in the environment due to its water solubility.


12.5 Results of PBT and vPvB assessment: PBT/vPvB assessment: No data available.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be emptied before discarding. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 1992

Shipping Name: Flammable liquids, toxic, n.o.s. (Nitromethane Methanol)

Hazard Class: 3, (6.1)

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

14.2 IMDG Transport Information



ID No.: UN 1992

Shipping Name: FLAMMABLE LIQUIDS, TOXIC, N.O.S. (Nitrocarbol Carbinol)

Hazard Class: 3, (6.1)

Packing Group: II

Flash Point: 11°C - closed cup

EmS Number: F-E, S-D

Label: Flammable, Toxic

Placard: Flammable, Toxic

14.3 UN Transport Information



ID No.: UN 1992

Shipping Name: Flammable liquids, Toxic, n.o.s. (Nitromethane Methanol)

Hazard Class: 3, (6.1)

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

Toxic Release Inventory (TRI): This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
75-52-5	Nitromethane	50%
67-56-1	Methanol	50%

This information must be included in all SDSs copied and distributed for this material.

CERCLA Hazardous Substances and corresponding RQs: Carbinol 5000 pounds

SARA Community Right-to-Know Program: Nitromethane, Carbinol

Clean Water Act: None

Clean Air Act: None

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

OSHA: All ingredients are regulated by 29 CFR1910.1200

State Regulations California prop. 65



Warning: This product can expose you to chemicals Nitromethane CAS # 75-52-5 and Methanol CAS # 67-56-1, known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey: All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 International Regulations:

Australian Inventory of Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product are on the Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product) are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and that they assume the risk of its use.

16.2 References: CHEMpendium database of Canadian Centre for Occupational Health and Safety (CCOHS), European Chemical Agency Database, and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC in-country emergency dial numbers

Country	Greeting Language	City	Local Number	Toll-Free number
Argentina	Latin American Spanish	Buenos Aires	54-1159839431	
Brazil	Portuguese	Rio De Janeiro	55-2139581449	
Brazil	Portuguese	Sao Paulo	55-1143491359	

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Brazil - Toll-Free	Portuguese		0800 892 0479	0800 892 0479
Cayman Islands	English	Local (National)	345-749-8392	
Chile	Latin American Spanish	Santiago	56 2 2581 4934	
Colombia	Latin American Spanish		01800-710-2151	01800-710-2151
Costa Rica	Latin American Spanish		506-40003869	
Dominican Republic	Latin American Spanish	Santo Domingo	1 (829) 956-7588	
El Salvador	Latin American Spanish	San Salvador	503 2136 7633	
Grenada	English	St George	1 (473) 230-0165	
Guinea	French		224 660 71 03 00	
Mexico	Latin American Spanish		01-800-681-9531	01-800-681-9531
Panama	Latin American Spanish		507-8322475	
Peru	Latin American Spanish	Lima	51-17071295	
Trinidad and Tobago	English	National Number	1-868-224-5716	
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141
Indonesia	Indonesian		001-803-017-9114	001-803-017-9114
Israel	Hebrew	Tel Aviv	972-37630639	
Japan	Japanese	Tokyo	81-345209637	
Malaysia	Malay	Kuala Lumpur	60-392125794	1-800-815-308
Philippines	Tagalog	Manila	+63 2 8395 3308 and 1-800-1-116-1020	1-800-1-116-1020
Russia	Russian		8-800-100-6346	8-800-100-6346
Saudi Arabia	Arabic and English		966-8111095861	
Singapore	English and Mandarin		65-31581349	800-101-2201
South Korea	Korean			003-0813-2549 and 080-822-1374
Taiwan	Mandarin	Taipei	886-2-7741-4207	00801-14-8954
Thailand	Thai		001-800-13-203-9987	001-800-13-203-9987
Australia	English	Sydney	61-290372994	
New Zealand	English	Auckland	64-98010034	
South Africa	English	None	0-800—983-611	0-800—983-611

Nitro 50-50

Conforms to OSHA 29 CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

16.4 SJC Compliance Education Inc. (SJC) did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by VP Racing Fuels Inc. or was reproduced from publicly available regulatory data sources and product SDSs. SJC makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability concerning the use of this information or the substance described in this SDS.

16.5 SDS Preparation Date 03/17/2015

SDS Previous Issue Date: None

SDS Revision Date: 05/18/2017 Sections revised 2,4,8,9,11 &14

SDS Revision Date: 08/06/2018 Sections revised 3,8,11,14,15,16

SDS Revision Date: 06/22/2019 Section revised 15

SDS Revision Date: 01/31/2020 Section revised 2,11,12,15,16

SDS Revision Date: 06/29/2021 Section revised 2,3,8,11,12,14,15,16

SDS Revision Date: 02/22/2023 Section revised 2,3,8,11,12,14,15,16

SDS Revision Date: 08/25/2023 Section revised 2,3,8,11,12,14,15,16

Prepared by SJC Compliance Education, Inc.

133 N Friendswood Dr.#181

Friendswood TX. 77546

steve@sjcedu.org

END OF SAFETY DATA SHEET